

ESPREE

Basin Mixer EP02C
All Pressures
Min. Pressure 35kpa
10 Year Warranty



FORENO.



Congratulations on your purchase of this high quality product from Foreno Tapware (NZ) Ltd. Please read the following before installation and retain for future reference.

Tech Specifications

Max. Operating Temperature 65 deg. Celsius, maximum operating pressure 500kPa.

Configuration:

- Mains Pressure systems - Remove the valve insert from the valve nipple and change aerator to the WELs rated one supplied.
- Unequal Low Systems - Ensure the valve nipple is attached to the cold in-feed hose (flow arrow aligned to the water flow).
- Equal Low systems - Remove the all valve insert from the valve nipples (minimum of 40 kPa required).

Installation

For pressures exceeding 500kPa, install a pressure reducing valve. Failure to do so may void the warranty. See Warranty section for more information.

- Position tap in 35mm hole, making sure the seal between tap and supporting surface is in place.
- Anchor to bench with fittings pack (Note: Use Foreno tube socket tool provided).
- Where applicable, it is important to ensure the base ring is hand-tight on the mixer, prior to installation.
- Thoroughly flush all pipes to eliminate any remaining dirt and residue and install inline filters
- Connect supply hoses to plumbing connections.

Maximum bend for flexible hose is 35mm radius. Do not stretch, crush or twist hoses. Do not swage hose ends.

Turn on mains supply. Check for leaks.

Mr Plumber: Do not pressure test this mixer under static pressure.

FORENO TAPWARE (NZ) LTD, 5 Hewlett St, Port Whangarei.

Tel: 64-9-470 2090

www.foreno.co.nz

Attached proof of
purchase here



Warranty

Congratulations on your purchase of this high quality product from Foreno Tapware (NZ) Ltd.

Foreno New Zealand warrants that high quality materials and workmanship have been used in the manufacture of its tapware. If the product fails due to a fault of manufacture, Foreno NZ, will at its option repair or replace the product, provided that:

- The proof of purchase is given to Foreno.
- That such defect shall be found to the Company's satisfaction to have arisen from faulty design, workmanship or materials.

The Company will not be liable due to:

- Failure to produce the original invoice, providing date of purchase;
- Damages incurred during installation;
- The installation not conforming with fitting instructions;
- Unauthorised modifications or repairs;
- Surface deterioration due to cleaning methods not in accordance with instructions.
- The following standards not being met:
 - Installation to comply with Section 5.4 of AS/NZS 3500 Standard with regard to Isolating stop cock use
 - As per AS/NZS 3500.1:2300 clause 3.3.4, the maximum operating pressure at any outlet, other than a fire service outlet, within a building does not exceed 500kPa.

The Company shall accept no responsibility for compensation towards assembly or disassembly of the fitting and shall not be liable for consequential loss or damage of any kind whatsoever to or in any way caused by the goods or their use.

Care & Maintenance

Chrome-plated finishes should not be cleaned with astringent, abrasive or citric cleaners. A soft damp cloth is recommended for cleaning. Mild soap solution can also be used on occasion.

In the unlikely event that this product fails during its warranty period, phone 0508 FORENO customer service free line, as unauthorised removal may void the warranty.

For domestic use only.

Thank you for purchasing Foreno Tapware.

Business Partner and proud supporter of
Master Plumbers, Gasfitters and Drainlayers.

