
FORENO.

TAPWARE MADE FOR NEW ZEALAND since 1969



EZYFLO Sink Mixer
Chrome **EZF10LFCH**

LEAD-FREE

Congratulations on your purchase of this high quality product from Foreno Tapware.
Please read the following before installation and retain (along with your receipt) for future reference.

TECHNICAL SPECIFICATIONS

Suitable for All Pressures
Minimum Pressure = 35kPa
Maximum operating Pressure = 500kPa* (As per NZ Building Code AS/NZ 3500)
Maximum operating Temperature = 65 deg. Celsius

For domestic use only.

CONFIGURATION

Mains Pressure systems	Remove the valve insert from the valve nipple and change aerator to the WELs rated one supplied.
Unequal Low Systems	Ensure the valve nipple is attached to the cold in-feed hose (flow arrow aligned to the water flow).
Equal Low systems	Remove the valve insert from the valve nipple.

***Note: any flow controller incorporated in the outlet to be tightened to prevent removal by hand.**

INSTALLATION

***FOR PRESSURES EXCEEDING 500kPa INSTALL A PRESSURE REDUCING VALVE. THOROUGHLY FLUSH ALL PIPES TO ELIMINATE ANY REMAINING DIRT AND RESIDUE, AND INSTALL INLINE FILTERS. FAILURE TO DO SO MAY VOID THE WARRANTY. TO BE INSTALLED AS PER THE REQUIREMENTS WITH AS/NZS 3500.**

Position tap in 35mm hole, making sure the seal between tap and supporting surface is in place.

Anchor to bench with fittings pack.

Thoroughly flush all pipes to eliminate any remaining dirt and residue and install inline filters.

Connect supply hoses to plumbing connections. NB: Maximum bend for flexible hose is 35mm radius. Do not stretch, crush or twist hoses. Do not swage hose ends.

Turn on mains supply. Check for leaks.
Plumbers Note: Do not pressure test this mixer under static pressure.