




FORENO.

EzyFlo 15mm Sink Taps EZ F3A



Congratulations on your purchase of this high quality product from Foreno Tapware.
Please read the following before installation and retain (along with your receipt) for future reference.

TECHNICAL SPECIFICATIONS

Suitable for All Pressures

- Minimum Pressure = 17kPa
- Maximum operating Pressure = 500kPa
- Maximum operating Temperature = 65 deg. Celsius

For domestic use only.

CONFIGURATION

- Mains Pressure systems Remove the aerator insert from the housing and change to the mains pressure insert supplied. See diagram.
- Unequal Low Systems Install as supplied.
- Equal Low systems Install as supplied.

INSTALLATION

For pressures exceeding 500kPa install a pressure reducing valve. Failure to do so may void the warranty.


- Cut 15mm screwed tube to allow for a minimum 15mm wall protrusion and install. NB: it is essential to apply either Teflon sealing tape or graphite & hemp around the screwed tube prior to installation
- Turn on water supply
- Check for leaks

WARRANTY

Please refer to our website for warranty information: www.foreno.co.nz/warranty

In the unlikely event that this product fails during its warranty period, phone our Customer Service team immediately on 0508 FORENO (0508 367 366) – as unauthorised removal of the product may void the warranty.

Changing Aerator for Mains Pressure only



ATTACH PROOF OF PURCHASE HERE

CARE AND MAINTENANCE

Chrome-plated finishes should not be cleaned with astringent, abrasive or citric cleaners. A soft, damp cloth is recommended for cleaning. Mild soap solutions can also be used on occasion.

PROUD PARTNER AND SUPPORTER OF MASTER PLUMBERS, GASFITTERS AND DRAINLAYERS

