




# FORENO.

## Shower Rose FDSR1



9 421027 593015



Congratulations on your purchase of this high quality product from Foreno Tapware.  
Please read the following before installation and retain (along with your receipt) for future reference.

### TECHNICAL SPECIFICATIONS

#### Suitable for All Pressures

Minimum Pressure = 35kPa

Maximum operating Pressure = 500kPa

Maximum operating Temperature = 65 deg. Celsius

For domestic use only.

### CONFIGURATION

Mains Pressure systems Install as supplied.


Unequal Low Systems Remove the flow restrictor from the ball joint and replace with the rubber washer (supplied).

Equal Low systems Remove the flow restrictor from the ball joint and replace with the rubber washer (supplied).

### INSTALLATION

**For pressures exceeding 500kPa install a pressure reducing valve. Failure to do so may void the warranty.**

- Screw the shower arm to the wall connection and tighten, using a liberal amount of teflon thread tape or hemp and grease at the wall connection (see diagram)
- Turns on water supply
- Check for leaks



ATTACH PROOF OF PURCHASE HERE

#### WARRANTY

Please refer to our website for warranty information: [www.foreno.co.nz/warranty](http://www.foreno.co.nz/warranty)

In the unlikely event that this product fails during its warranty period, phone our Customer Service team immediately on 0508 FORENO (0508 367 366) – as unauthorised removal of the product may void the warranty.

#### CARE AND MAINTENANCE

Chrome-plated finishes should not be cleaned with astringent, abrasive or citric cleaners. A soft, damp cloth is recommended for cleaning. Mild soap solutions can also be used on occasion.

PROUD PARTNER AND SUPPORTER OF MASTER PLUMBERS, GASFITTERS AND DRAINLAYERS



**Master Plumbers**  
Representing Excellence



**Master Gasfitters**  
Representing Excellence



**Master Drainlayers**  
Representing Excellence