



Single Hole Faucet **FSF9** 



Congratulations on your purchase of this high quality product from Foreno Tapware. Please read the following before installation and retain (along with your receipt) for future reference.

### **TECHNICAL SPECIFICATIONS**

# Suitable for All Pressures

Minimum Pressure = 17kPa Maximum operating Pressure = 500kPa Maximum operating Temperature = 65 deg. Celsius

For domestic use only.

## CONFIGURATION

Mains Pressure systems Remove the low pressure aerator and insert the mains pressure aerator supplied.

Unequal Low Systems Install as supplied.

Equal Low systems Install as supplied.

#### INSTALLATION

For pressures exceeding 500kPa install a pressure reducing valve. Failure to do so may void the warranty.

- Drill a 35mm hole on the bench.
- Connect the hoses to plumbing.
- Turn on water supply
- Check for leaks

#### WARRANTY

Please refer to our website for warranty information: www.foreno.co.nz/warranty

In the unlikely event that this product fails during its warranty period, phone our Customer Service team immediately on 0508 FORENO (0508 367 366) – as unauthorised removal of the product may void the warranty.

#### CARE AND MAINTENANCE

Chrome-plated finishes should not be cleaned with astringent, abrasive or citric cleaners. A soft, damp cloth is recommended for cleaning. Mild soap solutions can also be used on occasion.

PROUD PARTNER AND SUPPORTER OF MASTER PLUMBERS, GASFITTERS AND DRAINLAYERS

Master

Gasfitters

Master

Drainlayers

Master

Plumbers<sup>•</sup>