


# **PRIMUS** 15mm Sink Taps Chrome **PEB1A**





Congratulations on your purchase of this high quality product from Foreno Tapware. Please read the following before installation and retain (along with your receipt) for future reference.

## **TECHNICAL SPECIFICATIONS**

#### **Suitable for All Pressures**

Minimum Pressure = 17kPa Maximum operating Pressure = 500kPa Maximum operating Temperature = 65 deg. Celsius

For domestic use only.

### CONFIGURATION

Mains Pressure systems Remove the aerator insert from the housing and change to the mains pressure insert


supplied. See picture below for reference.

Unequal Low SystemsInstall as supplied.Equal Low systemsInstall as supplied.

# INSTALLATION

For pressures exceeding 500kPa install a pressure reducing valve. Failure to do so may void the warranty.

- Cut 15mm screwed tube to allow for a minimum
- 15mm wall protrusion and install. NB: It is essential
- to apply either Teflon sealing tape or graphite &
- hemp around the screwed tube prior to installation.
- Turn on water supply. Check for leaks.



#### WARRANTY

Please refer to our website for warranty information: www.foreno.co.nz/warranty

In the unlikely event that this product fails during its warranty period, phone our Customer Service team immediately on 0508 FORENO (0508 367 366) – as unauthorised removal of the product may void the warranty.

#### CARE AND MAINTENANCE

## NOT TO BE CLEANED WITH ASTRINGENT, ABRASIVE OR CITRIC CLEANERS.

A soft, damp cloth is recommended for cleaning. Mild soap solutions can also be used on occasion.

PROUD PARTNER AND SUPPORTER OF MASTER PLUMBERS, GASFITTERS AND DRAINLAYERS



FORENO TAPWARE (NZ) LTD | Freephone: 0508 FORENO | info@foreno.co.nz | 5 Hewlett Street, Port Whangarei 0110 | FORENO.CO.NZ